



Raw Product Information



Raw is a coated fine paper available in sheets and reels for offset printing.

Technical specifications

Parameter	Standard	Unit							
Basis weight	ISO 536	g/m ²	115	135	150	170	200	250	300
Brightness (illuminant D65/10°)	ISO 2470-2	%	104	104	104	104	104	104	104
CIE whiteness (D65/10°)	ISO 11475	%	144	144	144	144	144	144	144
Opacity	ISO 2471	%	96	97	98	99	>99	>99	>99
Roughness Bendtsen	ISO 8791-2	ml/min	< 450	< 450	< 450	< 450	< 450	< 500	< 550
Thickness	ISO 534	µm	138	162	180	204	240	300	360
Bulk	ISO 534	cm ³ /g	1.20	1.20	1.20	1.20	1.20	1.20	1.20
Relative humidity (23°C)	TAPPI 502	%	50	50	50	50	50	50	50

Mill Certification

- 

The environmental performance is monitored and continuously improved according to the requirements of Eco-Management and Audit Scheme (EMAS).
- 

The quality of the manufacturing is managed according to the requirements of ISO 9001.
- 

The environmental aspects of the mill are managed according to the requirements of ISO 14001.
- 

The energy consumed and the emissions generated by the mill are managed according to ISO 50001.
- 

All fibers from sustainability and controlled sources. FSC® may have limited availability, please check with your local sales office.
- 

All fibers from sustainability and controlled sources. PEFC™ may have limited availability, please check with your local sales office.
- 

The health and safety of the mill employees are managed according to the requirements of ISO 45 001.

Product Certification

- 

All fibers from sustainable and controlled sources. PEFC may have limited availability, please check with your local sales office.
- 

All fibers from sustainable and controlled sources. FSC may have limited availability, please check with your local sales office.
- 

Archivability tested according to the requirements of DIN 6738, Lifespan class - LDK 6-70.
- 

Pulp is bleached without the use of chlorine (ECF).
- 

Dry toner: Suitable for dry toner.